

SPECIFICATIONS


Dimension	Metric	British
Max. Working Height(Indoor) A	13.80m	45ft 3in
★ Max. Working Height(Outdoor)	11.20m	36ft 9in
Max. Platform Height(Indoor) B	11.80m	38ft 9in
★ Max. Platform Height(Outdoor)	9.20m	30ft 2in
Overall Length C	2.48m	8ft 2in
Overall Width D	1.19m	3ft 11in
Overall Height(Rails Up) E	2.62m	8ft 7in
Overall Height(Rails Down) F	2.09m	6ft 10in
Platform Size(Length ×Width)	2.27m×1.12m	7ft 5in×3ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in 0in/6ft
Turning Radius(Inside/Outside)	0m/2.10m	11in
Tyres	φ381×127mm	φ381×127mm

Performance		
S.W.L	350kg	771lb
S.W.L on Extension	113kg	249lb
Max. Occupants (Indoor/Outdoor)	3/0	3/0
★ Max. Occupants (Indoor/Outdoor)	3/1	3/1
Gradeability	25%	25%
Travel Speed(Stowed)	6.0km/h	3.73mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	52/52sec	52/52sec

Weight		
Overall Weight	3210kg	7076lb

Power		
Hydraulic Tank	20L	5.3gal
Lithium Battery	28.8V/175Ah	28.8V/175Ah
Charger	28V/30A	28V/30A
Driving Motor	2×15VAC/0.87kW	2×15VAC/0.87kW
Lifting Motor	15VAC/3.42kW	15VAC/3.42kW

Note: Parameters with "★" are optional



FEATURES

Standard Items

- Proportional Joystick Controls
- Tie-Down And Lifting Points
- Self-lock Gate On Platform
- Platform Load Sense System
- Drivable At Full Height
- Non-Emergency Stop Button
- Marking Tires
- Two-Wheel Drive
- Hydraulic oil receiver
- Two-Wheel Steering
- Automatic pure electric steering system
- Brake System
- Emergency Descent
- Kinetic energy recovery system
- System
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Alarm
- All Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- One-Way Platform Extension Deck
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road,Deqing,Zhejiang P.R.C 313219

Telephone: +86(572)8681688

E-Mail: export@cndingli.com

<https://en.cndingli.com>

Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission.

2024-02

